

SDS ATTACHMENT

PLEASE ATTACH THIS COMPLETED SHEET TO THE SDS FOR:

PRODUCT:

ZG90 BRUSHING 900ml

DATE:

31-Jan-18

(SDS date)

1. Manufacturer/Supplier:

Tradegear Ltd
Level 1, 99 Clarence Street
Riccarton
Christchurch 8011
New Zealand
Phone: 0800 22 44 34 or +64 3 341 8055
Fax: 0800 22 11 51 or +64 9 522 8833
24 hr emergency contact: +64 21 510 622
Website: www.tradegear.co.nz
Email: office@tradegear.co.nz

Emergency Information:

National Poison Centre: 0800 764 766
Chemcall 24/7 Emergency Response Service: 0800 243 622

2 & 15. Hazards Identification & Regulatory Requirements:

Product Name:	ZG90 Brushing
Group Standard, Approval #	Surface Coatings and Colourants (Flammable) Group Standard 2017 — HSR002662
HSNO Classes (from GHS codes)	3.1B, 6.1E, 6.3B, 6.4A, 6.9B, 9.1B
Class 9 Hazard/Precautionary Statements	DANGER Highly flammable liquid and vapour. May be harmful if swallowed. Causes mild skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Keep out of reach of children. Read label and Safety Data Sheet before use. If medical advice is needed, have product container or label at hand. Avoid release to the environment. Collect spillage.
TEL or EEL applicable?	None

Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ZG-90
Bulk

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

CRC Industries UK Ltd.
Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom
Tel.: +44 1278 727200
Fax.: +44 1278 425644
E-mail : hse.uk@crcind.com

1.4. Emergency telephone number

(+44)(0)1278 72 7200 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Physical:	Flammable liquid, category 2 Highly flammable liquid and vapour.
Classification is based on test data.	
Health:	Eye irritation, category 2 Causes serious eye irritation. Specific target organ toxicity - single exposure, category 3 May cause drowsiness or dizziness.
Classification based on calculation method.	
Environment:	Hazardous to the aquatic environment, chronic category 2 Toxic to aquatic life with long lasting effects.
Classification based on calculation method.	
Other hazards :	Repeated exposure may cause skin dryness or cracking.






Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008

Product identifier:	Contains: n-butyl acetate acetone; propan-2-one; propanone
Hazard pictogram(s):	  
Signal word:	Danger
Hazard statement(s):	H225 : Highly flammable liquid and vapour. H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness. H411 : Toxic to aquatic life with long lasting effects.
Precautionary statement(s):	P102 : Keep out of reach of children. P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 : Keep container tightly closed. P312 : Call a POISON CENTER or doctor/physician if you feel unwell. P337/313 : If eye irritation persists: Get medical advice/attention. P403/235 : Store in a well-ventilated place. Keep cool. P405 : Store locked up. P501-2 : Dispose of contents/container to an authorised waste collection point.
Supplemental Hazard information:	Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable.

3.2. Mixtures

Hazardous ingredient	Registration number	CAS-nr.	EC-nr	w/w %	Hazard Class and Category	Hazard statement	Notes
n-butyl acetate	01-2119485493-29	123-86-4	204-658-1	25-50	Flam. Liq. 3, STOT SE 3	H226,H336	
acetone; propan-2-one; propanone	01-2119471330-49	67-64-1	200-662-2	10-25	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3	H225,H319,H336	A
1-methoxy-2-propanol; monopropylene glycol methyl ether	01-2119457435-35	107-98-2	203-539-1	2.5-10	Flam. Liq. 3, STOT SE 3	H226,H336	A
Naphtha (petroleum), hydrotreated heavy	01-2119486659-16	64742-48-9	265-150-3	2.5-10	Asp. Tox. 1	H304	B,P



Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

aluminium powder (stabilized)	01-2119529243-45	7429-90-5	231-072-3	2.5-10	Water-react. 2, Flam. Sol. 1	H261,H228	A
zinc oxide	01-2119463881-32	1314-13-2	215-222-5	1-5	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	B
zinc powder - zinc dust (stabilized)	01-2119467174-37	7440-66-6	231-175-3	1-5	Aquatic Acute 1, Aquatic Chronic 1	H400,H410	

Explanation notes

A : substance with Community workplace exposure limit

B : substance with national established workplace exposure limit

P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)

(* Explanation phrases : see chapter 16)

SECTION 4: First aid measures**4.1. Description of first aid measures**

Contact with eyes :	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Contact with skin :	Wash with water and soap. Seek medical attention if irritation persists
Inhalation :	Fresh air, keep warm and at rest. Seek medical attention if ill effects occur
Ingestion :	If swallowed do not induce vomiting Seek medical advice

4.2. Most important symptoms and effects, both acute and delayed

Inhalation :	Excessive inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	May cause gastrointestinal disturbances Symptoms : sore throat, abdominal pain, nausea, vomiting
Skin contact :	Mildly irritating to skin Symptoms : redness and pain
Eye contact :	Irritating to eyes Symptoms : redness and pain, impaired vision

4.3. Indication of any immediate medical attention and special treatment needed

General Advice :	If you feel unwell, seek medical advice (show the label where possible) If symptoms persist always call a doctor
-------------------------	---

SECTION 5: Firefighting measures**5.1. Extinguishing media**

foam, carbon dioxide or dry agent

5.2. Special hazards arising from the substance or mixture

3 / 10

CRC Industries UK Limited
 Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6
 4DD
 Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.actioncan.com

Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

May form explosive vapour/air mixtures
Forms hazardous decomposition products
CO,CO2

5.3. Advice for firefighters

Keep container(s) exposed to fire cool, by spraying with water
In case of fire, do not breathe fumes

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Shut off all ignition sources
Ensure adequate ventilation
Wear suitable protective clothing including eye/face protection.

6.2. Environmental precautions

Do not allow to enter public sewers and watercourses

6.3. Methods and material for containment and cleaning up

Absorb spillage in suitable inert material

6.4. Reference to other sections

For further information see section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from heat and sources of ignition
Take precautionary measures against static discharges
Equipment should be earthed
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Do not breathe aerosols or vapours.
Ensure adequate ventilation
Avoid contact with skin and eyes.
Wash thoroughly after use
Wear protective gloves/protective clothing/eye protection/face protection.
Eyewash bottles should be available

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed, in a cool, well ventilated place.



Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

Keep out of reach of children.

7.3. Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

Hazardous ingredient	CAS-nr.	method	
EU established exposure limits:			
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
National established exposure limits, United Kingdom			
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
n-butyl acetate	123-86-4	TWA	150 ppm
		STEL	200 ppm
acetone; propan-2-one; propanone	67-64-1	TWA	500 ppm
		STEL	1500 ppm

8.2. Exposure controls

Control procedures :	Ensure adequate ventilation Keep away from heat and sources of ignition Take precautionary measures against static discharges
Personal protection :	Take precautions to avoid contact with skin and eyes when handling the product. It is good practice to wear gloves and to provide adequate ventilation whenever using the product. In all cases handle and use the product in accordance with good industrial hygiene practices.
inhalation :	In case of insufficient ventilation, wear suitable respiratory equipment.
recommended respiratory protection:	Air purifying respirator equipped with organic gas/vapor cartridge (type A)
hands and skin :	Wear suitable protective gloves against chemicals. Check the appropriateness of the recommended gloves for your own particular conditions of use and replace gloves regularly after check for signs of damage or defects.
Recommended gloves:	Nitrile
eyes :	Wear safety eyewear according to EN 166.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties



5 / 10

CRC Industries UK Limited
 Wylds Road, Castlefield Industrial Estate, Bridgwater, Somerset, TA6
 4DD
 Tel: +44 (0)1278 727200 Fax: +44 (0)1278 425644 web: www.actioncan.com

Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

Apperance : physical state : Viscous liquid.
colour : Grey.
odour : Characteristic odor.
pH : Not applicable.
Boiling point/range : Not available.
Flash point : - 18 °C
Explosion limits : upper limit : Not available.
lower limit : Not available.
Vapour pressure : Not available.
Relative density : 1.17 g/cm³ (@ 20°C).
Auto-ignition : > 200 °C
Viscosity : 80 ku

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reactions known if used for its intended purpose

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose

10.4. Conditions to avoid

Avoid overheating

10.5. Incompatible materials

Strong oxidising agent

10.6. Hazardous decomposition products

CO,CO₂

SECTION 11: Toxicological information

11.1. Information on toxicological effects

acute toxicity: based on available data the classification criteria are not met
skin corrosion/irritation: based on available data the classification criteria are not met



Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

serious eye damage/irritation: Causes serious eye irritation.
respiratory or skin sensitisation: based on available data the classification criteria are not met
germ cell mutagenicity: based on available data the classification criteria are not met
carcinogenicity: based on available data the classification criteria are not met
toxicity for reproduction: based on available data the classification criteria are not met
STOT-single exposure: May cause drowsiness or dizziness.
STOT repeated exposure: based on available data the classification criteria are not met
aspiration hazard: based on available data the classification criteria are not met

Information on likely routes of exposure:

Inhalation : Excessive inhalation of vapours may give rise to irritation and affect the nervous system
Skin contact : Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
Eye contact : Irritating to eyes

Toxicological data :

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LD50 oral rat	4016 mg/kg
		LC50 inhal.rat	27596 mg/l
		LD50 derm.rabit	2000 mg/kg
n-butyl acetate	123-86-4	LD50 oral rat	10760 mg/kg
		LC50 inhal.rat	> 20 mg/l
		LD50 derm.rabit	> 1400 mg/kg
zinc oxide	1314-13-2	LC50 inhal.rat	> 5.7 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	LD50 oral rat	> 2000 mg/kg
		LD50 derm.rabit	> 2000 mg/kg
acetone; propan-2-one; propanone	67-64-1	LD50 oral rat	> 5800 mg/kg
		LC50 inhal.rat	76 mg/l
		LD50 derm.rabit	> 15800 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, chronic category 2
 Toxic to aquatic life with long lasting effects.

Ecotoxicological data:

Hazardous ingredient	CAS-nr.	method	
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	LC50 fish	6812 mg/l
		EC50 daphnia	23300 mg/l



Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

n-butyl acetate	123-86-4	IC50 algae	647 mg/l
		LC50 fish	18 mg/l
		EC50 daphnia	44 mg/l
zinc oxide	1314-13-2	IC50 algae	0.136 mg/l
		LC50 fish	0.169 mg/l
		EC50 daphnia	1.7 mg/l
Naphtha (petroleum), hydrotreated heavy	64742-48-9	IC50 algae	> 1000 mg/l
		LC50 fish	> 1000 mg/l
acetone; propan-2-one; propanone	67-64-1	IC50 algae	530 mg/l
		LC50 fish	5540 mg/l
		EC50 daphnia	8800 mg/l

12.2. Persistence and degradability

No information available

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

No information available

12.6. Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : This material and its container must be disposed of in a safe way.
Do not discharge into drains or the environment, dispose to an authorised waste collection point.

National regulations : Disposal should be in accordance with local, state or national legislation

SECTION 14: Transport information

14.1. UN number

UN-number : 1263



Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

14.2. UN proper shipping name

Proper shipping name: PAINT RELATED MATERIAL (Zinc Oxide - Solvent Naphtha (Petroleum), Light arom. / low boiling point Naphtha - Unspecified - Zinc Power)

14.3. Transport hazard class(es)

Class: 3
ADR/RID - Classification code: F1

14.4. Packing group

Packing group: II

14.5. Environmental hazards

ADR/RID - Environmentally hazardous: Yes
IMDG - Marine pollutant: Marine pollutant
IATA/ICAO - Environmentally hazardous: Yes

14.6. Special precautions for user

ADR/RID - Tunnelcode: (D/E)
IMDG - Ems: F-E, S-E

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Safety Data Sheet is compiled according to the current European requirements.
Regulation (EC) No 1907/2006 (REACH)
Regulation (EC) No 1272/2008 (CLP)

15.2. Chemical safety assessment

No information available

SECTION 16: Other information

*Explanation hazard statements: H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H228 : Flammable solid.



Productname : ZG-90
Ref.Nr.: BDS002318_3_20180131 (EN)

Creationdate : 31.01.18 Version : 1.0
Replaces:

H261 : In contact with water releases flammable gases.
H304 : May be fatal if swallowed and enters airways.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

acronyms and synonyms:

TWA = time weight average
STEL = short time exposure limit
VOC = volatile organic compounds
PBT = persistant bioaccumulative toxic
vPvB = very persitant very bioaccumulative

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

